



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
[www.uspto.gov](http://www.uspto.gov)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/759,230	01/20/2004	Gary Michael Everingham	051481-5143	6453

7590 04/07/2006

Siemens Corporation  
Intellectual Property Department  
170 Wood Avenue South  
Iselin, NJ 08830

EXAMINER
----------

FRISTOE JR, JOHN K

ART UNIT	PAPER NUMBER
----------	--------------

3751

DATE MAILED: 04/07/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

E

<b>Office Action Summary</b>	Application No. 10/759,230	Applicant(s) EVERINGHAM ET AL.	
	Examiner John K. Fristoe Jr.	Art Unit 3751	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 28 February 2006.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1, 2, 5-13, 15-17, 19, 20, 22-24 and 27-29 is/are pending in the application.  
     4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1, 2, 5-13, 15-17, 19, 20 and 22-24 is/are rejected.
- 7) ☒ Claim(s) 27-29 is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 20 January 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
     Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
     Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).  
     a) ☐ All    b) ☐ Some \* c) ☐ None of:  
         1. ☐ Certified copies of the priority documents have been received.  
         2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.  
         3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)  | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                                   | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)             |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## **DETAILED ACTION**

### ***Response to Arguments***

1. Applicant's arguments with respect to claims 1, 2, 5-13, 15-17, 19, 20, 22-24, and 27-29 have been considered but are moot in view of the new ground(s) of rejection. Since the new grounds of rejections were necessitated by Applicants' amendment the instant Office action is made final.

### ***Claim Objections***

2. Claims 19 and 20 are objected to because of the following informalities: claims 19 and 20 depend from claim 18, which has been canceled by Applicants. Appropriate correction is required.

### ***Claim Rejections - 35 USC § 103***

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

1. Claims 1, 2, 5, 6, 9, 10, 12, and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 5,680,880 (Miyake et al.) in view of U.S. Pat. No. 5,381,765 (Rhodes). Miyake et al. disclose a method of assembling, operating, and closing an exhaust gas recirculation valve comprising the steps of providing a base (1), a fluid conduit (1c), a first port (1a), a second port (1b), a valve member (3), a valve shaft (4) having a first end (lower portion in figure 5) and a second end (top portion in figure 5), mounting a linear actuator (34), a rotary motor (12), a displaceable member (41), wherein the displaceable member (41) contacts the valve shaft (4) to open the valve (col. 7, lines 35-39), wherein the displaceable member's end

Art Unit: 3751

and the valve shaft are in a spaced relationship (figure 5), a linear spring (11) engaging the valve shaft (via flange 7) that biases the valve member (3), a first cup (7), a valve seat (2), wherein the valve shaft (4) has a longitudinal axis (axis running vertically in figure 5), wherein the rotation axis (vertical axis in figure 5) is parallel to the longitudinal axis, wherein the displaceable member (41) has a disc-shaped member (portion that contacts the valve shaft has a circular face and therefore is the shape of a disc), wherein the spring (11) is between the valve member 93) and the actuator (34), a second flange member (54), and wherein the spring's send end contacts a base (adjacent the lead line for element 11 in figure 5) but lacks a second cup to retain the spring. Rhodes teaches a spring retainer mounted to a valve shaft comprising a shaft (13), a spring (19), a first cup (73) and a second cup (18). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the method of assembling, operating, and closing an exhaust gas recirculation valve of Miyake et al. by providing a second cup to retain the spring as taught by Rhodes in order to protect the valve body from the movement of the spring during operation of the valve.

2. Claims 7, 8, and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 5,680,880 (Miyake et al.) in view of U.S. Pat. No. 5,381,765 (Rhodes) as applied to claims 6, and 9 above, and further in view of U.S. Pat. No. 5,941,500 (Lebkuchner). Miyake et al. modified above, disclose a method of assembling, operating, and closing an exhaust gas recirculation valve comprising the steps of providing a base (1), a fluid conduit (1c), a first port (1a), a second port (1b), a valve member (3), a valve shaft (4) having a first end (lower portion in figure 5) and a second end (top portion in figure 5), mounting a linear actuator (34), a rotary motor (12), a displaceable member (41), wherein the displaceable member (41) contacts the valve shaft (4) to open the valve (col. 7, lines 35-39), wherein the displaceable member's end

Art Unit: 3751

and the valve shaft are in a spaced relationship (figure 5), a linear spring (11) engaging the valve shaft (via flange 7) that biases the valve member (3), a first cup (7), a valve seat (2), wherein the valve shaft (4) has a longitudinal axis (axis running vertically in figure 5), wherein the rotation axis (vertical axis in figure 5) is parallel to the longitudinal axis, wherein the displaceable member (41) has a disc-shaped member (portion that contacts the valve shaft has a circular face and therefore is the shape of a disc), wherein the spring (11) is between the valve member 93) and the actuator (34), a second flange member (54), and wherein the spring's send end contacts a base (adjacent the lead line for element 11 in figure 5) but lacks providing the second end of the valve shaft being curved. Lebkuchner teaches a method of assembling a valve assembly having a valve shaft (48) and wherein the valve shaft (48) has curved end portion (figure 5), a valve disc member (50), and a valve seat (38). It would have been obvious to one of ordinary skill in the art at the time the invention was made to further modify the method of assembling, operating, and closing an EGR valve having a valve shaft with a flat send end of Miyake et al. by machining the end of the valve shaft into a curve as taught by Lebkuchner in order to operate the valve assembly even if the valve shaft and the displaceable member become askew from each other.

3. Claims 15 and 22 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 5,680,880 (Miyake et al.) in view of U.S. Pat. No. 5,381,765 (Rhodes) applied to claims 1 and 9 above, and further in view of U.S. Pat. No. 6,484,704 (Cook et al.). Miyake et al. modified above, disclose a method of assembling, operating, and closing an exhaust gas recirculation valve comprising the steps of providing a base (1), a fluid conduit (1c), a first port (1a), a second port (1b), a valve member (3), a valve shaft (4) having a first end (lower portion in figure 5) and a second end (top portion in figure 5), mounting a linear actuator (34), a rotary motor (12), a displaceable member (41), wherein the displaceable member (41) contacts the

Art Unit: 3751

valve shaft (4) to open the valve (col. 7, lines 35-39), wherein the displaceable member's end and the valve shaft are in a spaced relationship (figure 5), a linear spring (11) engaging the valve shaft (via flange 7) that biases the valve member (3), a first cup (7), a valve seat (2), wherein the valve shaft (4) has a longitudinal axis (axis running vertically in figure 5), wherein the rotation axis (vertical axis in figure 5) is parallel to the longitudinal axis, wherein the displaceable member (41) has a disc-shaped member (portion that contacts the valve shaft has a circular face and therefore is the shape of a disc), wherein the spring (11) is between the valve member 93) and the actuator (34), a second flange member (54), and wherein the spring's send end contacts a base (adjacent the lead line for element 11 in figure 5) but lacks the method step of closing the valve in the even of a power failure. Cook et al. disclose a method of operating a rotary valve member comprising the step of closing the valve upon the event of a power failure (col. 3, lines 41-46). It would have been obvious to one of ordinary skill in the art at the time the invention was made to further modify the method of operating, closing and assembling a valve assembly of Miyake et al. by closing the valve upon a failure of power as taught by Cook et al. in order to avoid catastrophic damage downstream of the valve assembly.

4. Claims 16, 17, 19, 20, 23, and 24 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 5,680,880 (Miyake et al.) in view of U.S. Pat. No. 5,381,765 (Rhodes) and further in view of U.S. Pat. No. 6,484,704 (Cook et al.) as applied to claims 15 and 22 above, and further in view of U.S. Pat. No. 5,941,500 (Lebkuchner). Miyake et al. modified above, disclose a method of assembling, operating, and closing an exhaust gas recirculation valve comprising the steps of providing a base (1), a fluid conduit (1c), a first port (1a), a second port (1b), a valve member (3), a valve shaft (4) having a first end (lower portion in figure 5) and a second end (top portion in figure 5), mounting a linear actuator (34), a rotary motor (12), a

Art Unit: 3751

displaceable member (41), wherein the displaceable member (41) contacts the valve shaft (4) to open the valve (col. 7, lines 35-39), wherein the displaceable member's end and the valve shaft are in a spaced relationship (figure 5), a linear spring (11) engaging the valve shaft (via flange 7) that biases the valve member (3), a first cup (7), a valve seat (2), wherein the valve shaft (4) has a longitudinal axis (axis running vertically in figure 5), wherein the rotation axis (vertical axis in figure 5) is parallel to the longitudinal axis, wherein the displaceable member (41) has a disc-shaped member (portion that contacts the valve shaft has a circular face and therefore is the shape of a disc), wherein the spring (11) is between the valve member 93) and the actuator (34), a second flange member (54), and wherein the spring's send end contacts a base (adjacent the lead line for element 11 in figure 5) but lacks a the motor being a constant rate motor such as a synchronous motor. Lebkuchner teaches a method of operating a valve comprising the step of providing a constant rate synchronous motor (col. 5, lines 33-36). It would have been obvious to one of ordinary skill in the art at the time the invention was made to further modify the method of operating, closing and assembling a valve assembly of Miyake et al. by replacing the rotary motor with a rotary synchronous motor as taught by Lebkuchner in order for the motor to turn the actuator as a constant speed which reduced the effect on the flow of the fluid caused by the pressure differential between the two ports as the valve opens and closes.

*Allowable Subject Matter*

5. Claims 27-29 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

*Conclusion*

6. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than **SIX MONTHS** from the date of this final action.


7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to John K. Fristoe Jr. whose telephone number is (571) 272-4926. The examiner can normally be reached on Monday-Friday, 7: 00 a.m-4: 30 p.m.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Justine R. Yu can be reached on (571) 272-4835. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.



Art Unit: 3751

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).



John K. Fristoe Jr.  
Examiner  
Art Unit 3751

JKF



EDWARD K. LOOK  
SUPERVISORY PATENT EXAMINER  
TECHNOLOGY CENTER 3700

4/3/06